

KEY FEATURES

- Designed with the operator in mind, featuring familiar controls, Scissor style steering, ergonomic joystick and ease of entry/exit from platform.
- Lightweight and compact footprint is ideal for sensitive flooring and accessing tight spaces with high transportability.
- Increase productivity with longer running AGM batteries.
- Quick access to key, known scissor components and durable mast protection offers efficient serviceability to maximize uptime with new LCD display showing fault codes and maintenance information.



Performance

	Indoor	Outdoor
Platform Height (Elevated)	5.5 m	4 m
Working Height	7.5 m	6 m
Platform Capacity	181 kg	181 kg
Extension Deck Capacity	113 kg	113 kg
Number of Occupants	1	1
Lift / Lower Time†	23/23 seconds	23/23 seconds
Maximum Drive Height	Fully Elevated	4 m
Weight*	890 kg	890 kg
Drive Speed (Elevated)	0.8 km/h	0.8 km/h
Drive Speed (Lowered)	4 km/h	4 km/h
Gradeability	30%	30%
Turning Radius (Inside)	Zero	Zero
Turning Radius (Outside)	1.3 m	1.3 m

Machine Dimensions

Platform Height (Lowered)	1.98 m
Platform Entry Height	0.47 m
Platform Retracted (W x L)	0.75 m x 0.75 m
Platform Extended (W x L)	0.75 m x 1.30 m
Machine Width x Length	0.76 m x 1.35 m
Machine Length with Extension	1.46 m
Wheelbase	1.05 m
Ground Clearance	6.35 cm

Power Source

Battery	Four Sealed-AGM 6V - 220 AH (180 duty cycles)
Charger	27 amp
Drive	4 Brush Direct Electric Drive (Planetary Gear)

Lift & Steer Systems

Lift	Hydraulic
Steer	Scissor Style

Tyres

Front	0.25 m . 0.07 m Non-Marking
Rear	0.25 m x 0.07 m Non-Marking

Brakes

Electric

Standard Features

- Extension Platform with Drop Bar
- Active Pothole Protection System
- All Motion Alarm
- Multi-Function Universal Charger
- Analyzer Port for Diagnostics
- Battery Condition Indicator
- DC Electric Drive
- Dynamic Braking
- Electric Brake Release
- Fork Lift Pockets
- Greaseless Kingpin Joints
- Horn
- Hourmeter
- Lanyard Attach Points
- LCD Display for Fault Code Information
- Lifting and Tie Down Points
- Load Sensing System
- Maintenance Indicator
- Manual Descent
- Mast Maintenance Prop
- Onboard Diagnostic System
- Proportional Controls
- Amber Beacon
- USB/ Phone Cradle
- Tilt Alarm and Light
- Telematics Ready

Accessories & Options

- Ceiling Tile Platform (0.56 m x 0.66 m)
- Platform with Work Tray (0.71 m x 0.75 m)
- Anti-Vandalism Package
- CleanGuard™
- ClearSky™
- Crane Hook
- JLG Mobile Control
- Front and Side Bumpers
- Gate Alarm

The JLG "1 & 5" Warranty

JLG Industries, Inc., backs its products with its exclusive "1 & 5" Warranty. We provide coverage on all products for one (1) full year and cover all specified major structural components for five (5) years. Due to continuous product improvements, we reserve the right to make specification and/or equipment changes without prior notification. This machine meets or exceeds AS/NZS 1418.10 2011 as originally manufactured for intended applications.

JLG Industries (Australia)

358 Park Road
Regents Park, NSW 2143
Telephone 02 8718 6300
Fax 02 8718 6377
www.jlg.com.au

An Oshkosh Corporation Company